

BIAR RNP STAR RWY 19
Recommended Coding Tables

AFPAC 1M

Serial Number	Path Descriptor	Waypoint Identifier	Fly-over	Course / Track °M(°T)	Magnetic Variation	Distance (NM)	Turn Direction	Altitude (ft)	Speed (kt/h)	Navigation Specification
010	IF	AFPAC	-		+12.0			F100+		RNP 1
020	TF	AR702	-	053 (041.6)	+11.9	12.0		A7000+		RNP 1
030	TF	NORFI	-	082 (069.8)	+11.8	4.5		A6000+	-230	RNP 1

BEZIM 1M

Serial Number	Path Descriptor	Waypoint Identifier	Fly-over	Course / Track °M(°T)	Magnetic Variation	Distance (NM)	Turn Direction	Altitude (ft)	Speed (kt/h)	Navigation Specification
010	IF	BEZIM	-		+12.0			A7000+		RNP 1
020	TF	NORFI	-	108 (095.8)	+11.8	10.0		A6000+	-230	RNP 1

CUBAS 1M

Serial Number	Path Descriptor	Waypoint Identifier	Fly-over	Course / Track °M(°T)	Magnetic Variation	Distance (NM)	Turn Direction	Altitude (ft)	Speed (kt/h)	Navigation Specification
010	IF	CUBAS	-		+11.9			A7000+		RNP 1
020	TF	NORFI	-	175 (163.5)	+11.8	10.0		A6000+	-230	RNP 1

DORFA 1M

Serial Number	Path Descriptor	Waypoint Identifier	Fly-over	Course / Track °M(°T)	Magnetic Variation	Distance (NM)	Turn Direction	Altitude (ft)	Speed (kt/h)	Navigation Specification
010	IF	DORFA	-		+11.8			A7000+		RNP 1
020	TF	NORFI	-	204 (191.9)	+11.8	10.0		A6000+	-230	RNP 1

PERUR 1N

Serial Number	Path Descriptor	Waypoint Identifier	Fly-over	Course / Track °M(°T)	Magnetic Variation	Distance (NM)	Turn Direction	Altitude (ft)	Speed (kt/h)	Navigation Specification
010	IF	PERUR	-		+12.0			F110+		RNP 1
020	TF	AR706	-	063 (050.7)	+11.6	25.6		A7000+		RNP 1
030	TF	AKI	-	063 (051.4)	+11.5	5.0		A5600+	-180	RNP 1

PEXIL 1M

Serial Number	Path Descriptor	Waypoint Identifier	Fly-over	Course / Track °M(°T)	Magnetic Variation	Distance (NM)	Turn Direction	Altitude (ft)	Speed (kt/h)	Navigation Specification
010	IF	PEXIL	-		+11.5			F110+		RNP 1
020	TF	AR701	-	028 (017.0)	+11.4	19.3		A8000+		RNP 1
030	TF	ARLAX	-	014 (002.8)	+11.5	8.0		A6000+	-230	RNP 1

PEXIL 1N

Serial Number	Path Descriptor	Waypoint Identifier	Fly-over	Course / Track °M(°T)	Magnetic Variation	Distance (NM)	Turn Direction	Altitude (ft)	Speed (kt/h)	Navigation Specification
010	IF	PEXIL	-		+11.5			F110+		RNP 1
020	TF	AR703	-	028 (017.0)	+11.4	8.9		A8000+		RNP 1
030	TF	AR709	-	005 (353.7)	+11.6	7.0				RNP 1
040	TF	AKI	-	005 (353.7)	+11.5	6.0		A5600+	-180	RNP 1

MAMEP 1M

Serial Number	Path Descriptor	Waypoint Identifier	Fly-over	Course / Track °M(°T)	Magnetic Variation	Distance (NM)	Turn Direction	Altitude (ft)	Speed (kt/h)	Navigation Specification
010	IF	MAMEP	-		+11.2			F100+		RNP 1
020	TF	AR705	-	319 (307.6)	+11.4	9.8		A7000+		RNP 1
030	TF	ARLAX	-	319 (307.4)	+11.5	4.5		A6000+	-230	RNP 1

MAMEP 1N

Serial Number	Path Descriptor	Waypoint Identifier	Fly-over	Course / Track °M(°T)	Magnetic Variation	Distance (NM)	Turn Direction	Altitude (ft)	Speed (kt/h)	Navigation Specification
010	IF	MAMEP	-		+11.2			F100+		RNP 1
020	TF	AR707	-	313 (302.2)	+11.4	9.6		A7000+		RNP 1
030	TF	GITTA	-	313 (301.9)	+11.5	4.0		A6000+	-180	RNP 1

UTISU 1M

Serial Number	Path Descriptor	Waypoint Identifier	Fly-over	Course / Track °M(°T)	Magnetic Variation	Distance (NM)	Turn Direction	Altitude (ft)	Speed (kt/h)	Navigation Specification
010	IF	UTISU	-		+11.2			A7000+		RNP 1
020	TF	ARLAX	-	270 (258.9)	+11.5	11.7		A6000+	-230	RNP 1

UTISU 1N

Serial Number	Path Descriptor	Waypoint Identifier	Fly-over	Course / Track °M(°T)	Magnetic Variation	Distance (NM)	Turn Direction	Altitude (ft)	Speed (kt/h)	Navigation Specification
010	IF	UTISU	-		+11.2					RNP 1
020	TF	AR708	-	263 (252.0)	+11.4	7.2		A7000+		RNP 1
030	TF	GITTA	-	263 (252.0)	+11.5	5.0		A6000+	-180	RNP 1